



Diesel Powered Generators



*Shown on optional
TRLR10W trailer*

Dependable jobsite power

www.multiquip.com

DCA7000SSA1

Delivers dependable performance for a variety of industrial and commercial applications.

Compact, sound-attenuated package with full instrumentation, including hour meter and warning lights for oil, water and battery.

- 7kW maximum, 6kW continuous
- Brushless alternator design
- Ultra-clean AC power - voltage regulation $\pm 2.5\%$
- Quiet operation — 65 dBA @ 23 feet
- Full-panel GFCI protection that is OSHA and NEC compliant
- Dependable Tier 4 Kubota diesel engine

‡‡ Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. Multiquip Inc. and its subsidiary companies makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy of the engine power rating. Users are advised to consult the engine manufacturer's owners manual and its website for specific information regarding the engine power rating.

* See receptacle chart on Page 7.

** Electric start models are shipped less battery.

*** All running times computed at full load using fuel consumption rates supplied by engine manufacturer.

‡ Requires adapter kit.

Note: Some units may be shown with optional equipment.

All features and specifications are subject to change without notice.
Version (01-12_BD)
Units manufactured by Denyo Mfg. Co.

Connect with us on



SPECIFICATIONS

MODEL	DA7000SSA1
Alternator Design	Brushless
Maximum Watts	7,000
Continuous Watts	6,000
Voltage	120/240V
Max. Amp @ 120V	58.3
Cont. Amp @ 120V	50
Max. Amp @ 240V	29.2
Cont. Amp @ 240V	25
Frequency/Phase	60 Hz / Single phase
Voltmeter	Standard
Full Power Switch	N/A
RECEPTACLES* AND CIRCUIT BREAKERS	
5-20R 125V GFCI 20A	1
L5-30R 125V; T-Lock 30A	1
L14-30R 125/250V; T-Lock 30A	1
CS-6369; 125/250VAC 50A	1
Main Circuit Breaker	25A
Number of Poles	2
ENGINE	
Engine Manufacturer	Kubota Diesel
Engine Model	Z482
Horsepower (KW)‡‡	12.5 (9.3)
Rated Speed — RPM	3,600
Low Oil Shutdown	Standard
Starting Systems**	Electric
Fuel Capacity — gal (ltr)	6.6 (25)
Running Time — hr./tank***	10
Fuel Gauge	Standard
Automatic Idle Control	Standard
Sound Level dB @ 23 ft.	65
DIMENSIONS AND WEIGHT	
Length — in. (cm)	45 (114)
Width — in. (cm)	25½ (65)
Height — in. (cm)	31¼ (81)
Dry Weight — lbs. (kg)	527 (239)
OPTIONS	
Wheel Kit	WKT225A
Trailer	TRLR10W‡

© COPYRIGHT 2011, MULTIQUIP INC.



MULTIQUIP INC.
POST OFFICE BOX 6254
CARSON, CA 90749
310-537-3700 • 800-421-1244
FAX: 310-537-3927
E-MAIL: mq@multiquip.com
www.multiquip.com