

**MQ** MULTIQUIP



# Dual-Operator Welder/Generator

**Model DLW330X2**



**Single 340 Amp  
or Dual 200 Amp welding power**

**EXCLUSIVE FEATURE!**

**SmartStick**

*Innovative SmartStick technology automatically stops the engine if no welding or AC power is used for a preset time (1 minute to 30 minutes).*

*To restore power, the operator needs only to strike the welding stick.*

**Construction Starts Here**

[www.multiquip.com](http://www.multiquip.com)



# DLW330X2 Dual-Operator Welder/Generator

This CC (Constant Current) and CV (Constant Voltage) welder delivers up to 340 amps of operation for one man, or simultaneous two man operation with 200 amps of output per operator. Additionally, it provides up to 10.5 kW of 120/240 volt AC power. This is the welder that gives you more spark for your arc.

- **One or Two-man operation.** Independent controls and up to 200 amps for each operator or 340 amps for one operator.
- **E-Mode** improves fuel efficiency by allowing the operator to weld with the engine at idle speed at up to 200 amps. Greatly reduces operating costs and noise levels.
- **Arc Force Control** allows the operator to fine tune DC current during low voltage welding conditions and helps prevent electrodes from sticking during short arc length welding.
- **Dependable Kubota diesel engine** is backed by a three-year engine manufacturer's warranty. A standard self-priming fuel system allows quick starting even if the engine is run dry. Automatic idle control is standard for improved fuel economy.
- **Low noise level** produces only 61.3 dBA.
- **SmartStick** — this sensor automatically shuts off the engine during periods of no load and restarts it when the operator strikes the welding rod. The variable sensor — adjustable from one to 30 minutes — enables the operator to select the optimum working conditions and reduce fuel consumption.



Complete instrumentation simplifies operation.

Your Multiquip dealer is:

All features and specifications are subject to change without notice. MQDLW330X2 (1109)

## Specifications

MODEL	DLW330X2
<b>WELDER FEATURES</b>	
DC Voltage	31.2, 2x26.6CC; 28, 22.3CC
DC Current	280CC/CV 2x165CC/CV
100% Duty Cycle — amps	280
Current Range, amps	70-340, 2x35-200
DC Current — Constant Voltage	Standard
DC Current — Constant Current	Standard
Welding Process — SMAW	Standard
Welding Process — FCAW	Standard
Welding Process — GMAW	Standard
Welding Process — GTAW	Standard
Welding Process — ACAC	Standard
<b>AC OUTPUT</b>	
Maximum Output — kW Single Phase	10.5
Continuous Output — kW Single Phase	9.6
Cycle	60
Voltage	120/240
Voltage Regulation	±1.5
Receptacles (see chart below)	120/240V, 50A x1 240V, 30A x 1 120V, 30A x1 120V, 20A GFCI x1
<b>ENGINE FEATURES</b>	
Engine Model	Kubota D902
No. Cylinders; HP; RPM	3
Fuel Type	Diesel
Fuel Tank Capacity — gal.	9.5
Fuel Consumption at rated load — gph	1.1
Electric Start, Idle Switch	Standard
Noise Level dBA @ 23 ft.	61.3
<b>GENERAL FEATURES</b>	
Simultaneous Use — AC/DC	Standard
Lifting Bale	Standard
External Drains — Coolant	Standard
External Drains — Oil, Fuel	Standard
Automatic Safety Shutdown — Oil Pressure	Standard
Automatic Safety Shutdown — Coolant Temperature	Standard
Automatic Safety Shutdown — Thermal Overload	Standard
<b>DIMENSIONS AND WEIGHT</b>	
Dimensions — L x W x H in.	50.8 X 26.8 X 33.1
Dry Weight lbs.	893

© COPYRIGHT 2009, MULTIQIP INC.



**MULTIQIP INC.**  
 POST OFFICE BOX 6254  
 CARSON, CA 90749  
 310-537-3700 • 800-421-1244  
 FAX: 310-537-3927  
 E-MAIL: mq@multiquip.com  
 www.multiquip.com