

Transform your slab!

FirstPolish is a three-step process that enables you to:

- Attain superior levels of gloss and reflectivity with your power trowels.
- Achieve a higher level of surface refinement.
- Save time and money by compressing your project timeline.
- Reduce maintenance expenses and upkeep requirements over the life of the slab.

Ideal applications include floors in retail showrooms, airports, museums, institutional facilities such as hospitals and government buildings.



DAY ONE - 0 HOURS

Concrete Placement

Following screed application a check-rod is used to straighten the surface.



DAY ONE - 2-6 HOURS

With a rider trowel spray system **Step 1** is applied 4 times during the floating process and worked completely into the surface using a trowel equipped with float pans.



DAY ONE - 7-8 HOURS

The floor is troweled until the desired level of burnish/finish is achieved.



DAY ONE - 8 HOURS

Step 2 is applied once power troweling is completed and worked in with a foxtail broom, keep surface wet with product for 30 minutes.



DAY TWO - 1 - 2 HOURS

At the completion of major construction, but prior to delivering the project to the owner, surface is cleaned with an auto scrubber and water.



DAY TWO - 2 - 4 HOURS

Following use of auto scrubber surface is burnished with a black strip pad.




DAY TWO - 4 HOURS

Step 3 is applied and the surface is burnished with trowel blades and black strip pad. Repeat process until desired level of reflectivity is achieved.

Download **technical information** now.

EarthSmartTM

A benefit on jobs with LEED requirements



*Time stamps shown for illustrative purposes only. Actual setup times for concrete will vary according to mix designs and other environmental factors.