



MULTIQUIP



MULTIQUIP

Generators and Welders



Dependable jobsite power

Construction Starts Here

www.multiquip.com



Portable Generators



Also available with Recoil/Electric Start as Model GA-6HEA

Features available on all models except where noted.

Meet MultiQuip's newest generator models... the preferred generators of contractors everywhere!

- **Control Panel** — Rugged new look withstands the rough handling on the job site or in the back of a truck.
- **Receptacles** — Additional twist-lock receptacles have been added for operator convenience.
- **Lifting Bail** — Standard on 3.6 kW to 6 kW models. Hinged design lays flat when not in use.
- **Engines** — MultiQuip generators are now available with either Honda GX-Series or Robin EX-Series industrial grade engines.
- **Electric Start** — available on 6 kW models; standard on 9.7 kW model.
- **Brushless design** — low maintenance for years of dependable service.
- **Superior voltage regulation** — helps to keep tools and equipment running at optimal levels; helps them last longer.

Voltmeter

This feature serves as a convenient diagnostic tool on the jobsite. The operator can quickly tell whether or not the generator is producing the correct voltage and prevent overheating of expensive tools and equipment.



Silent Type Muffler

Reduces noise level on Honda units. USFS-approved spark arrestors standard on 2.5kW through 6kW Honda-powered models.

Reliability

GA-Series generators use a brushless design that minimizes maintenance by eliminating the carbon brushes and slip rings common on competitive models.

The best warranty in the industry.

All GA-Series generators are covered by a two-year parts and labor warranty.

There's a size and model for every application...



2500 watts max.
Honda engine
Recoil start
GA25H

2900 watts max.
Robin engine
Recoil start
GA29R



3600 watts max.
Honda engine
Recoil start
GA36HA

4500 watts max.
Robin engine
Recoil start
GA45RA



UWK Wheel Kit
For 2.5kw through 6kw models;
Shown with handles in both up and
down positions.





Portable Generators



6000 watts max.
Honda engine
Recoil/Electric start
GA6HEA

Also available with Robin engine as Model GA6REA



9700 watts max.
Honda engine
Recoil/Electric start
GA97HE



Unit shown on optional WKT97 Wheel Kit

Diesel Powered Generator

Delivers dependable performance for a variety of industrial and commercial applications.

Compact, sound-attenuated package with full instrumentation, including hour meter and warning lights for oil, water and battery.

- 7kW maximum, 6kW continuous
- Brushless alternator design
- 12.5 HP \ddagger water-cooled Kubota diesel engine
- Quiet operation — 65.7 dBA @ 23 feet



7000 watts max.
Kubota diesel engine
Electric start
DA7000SSA



Shown on optional TRLR10W trailer



High Cycle Generator

Simultaneously produces both 60 and 180 Hz power

The only choice for dual-use portable power.

Simultaneously produces standard 60 Hz power and 180 Hz power for "high-cycle" concrete vibrators. No other high-cycle generator is this versatile.

- **Rugged control panel** withstands rough handling
- **Powers up to three Multiquip 2" high-cycle vibrators** or two of our 2⁵/₈" vibrator heads (varies according to current requirements).
- **Lifting bail standard** — hinged design lays flat when not in use.
- **Engine** — powered by an 9.5 HP Honda GX-Series with low oil shutdown.



5kVA @ 180 cycle
4kW @ 60 cycle
Honda engine
Recoil start
GDP5H

60 Hz Single Phase Output		Engine		Dimensions and Weight	
Maximum Watts	4 kW	Engine Manufacturer	Honda	Length in. (cm)	28.34 (720)
Continuous Watts	3.6 kW	Engine Model	GX-160	Width in. (cm)	22.04 (560)
Voltage	120/240	Horsepower (kW)‡‡	9.5 (7.1)	Height in. (cm)	21.25 (540)
Max./Cont. Amp @ 120V	33.3 / 16.6	Rated Speed RPM	3,600	Dry Weight lb. (kg)	235 (107)
Max./Cont. Amp @ 240V	30 / 15	Low Oil Shutdown	Standard	Options	
180 Hz Three Phase Output		Starting System	Recoil	Wheel Kit	UWK
Continuous Watts	5 kVA	Fuel Capacity gal. (ltr)	4.0 (19)		
Voltage	240	Running Time hr/tnk**	5.5		
Cont. Amp @ 240V	12.5	Fuel Gauge	Standard		
Power Factor	80%	Automatic Idle Control	Standard		
Circuit Breaker	15 amp				
Receptacles*					
(1) 5-20R 125V GFCI					
(1) L5-30R 125V Twist-lock 30A					
(1) L6-20R 250V Twist-lock 20A (3) 7410 250V Twist Lock 20A					

* See Receptacle Chart, Page 7.
 ** Running time is computed at full load using fuel consumption rates supplied by engine manufacturer.
 ‡‡ See HP note on back page.



Portable Welders

Battery-powered welder

- Portable, powerful design with true DC power
- Up to 180 amps of welding power

Gasoline-powered welders

- Permanent magnet alternator design reduces overall weight.
- Simultaneous welding and AC output.
- Compact in size — easily fits on your service truck or in the basket of high-reach equipment.
- Powered by Honda gas engines with idle control and low oil shutdown standard.

Diesel-powered welders

- Kubota diesel engines reduce fuel cost and provide years of trouble-free operation.
- CC and CV welding capability on selected models.
- Optional remote control on 225 amp and larger machines
- Simultaneous welding and AC output.
- Three-year/3,000 hour parts and labor warranty on 225 amp and larger machines.

135 amp welder
1.5 kW AC output
Honda engine
GAW135H



180 amp welder
Battery powered
BDW180MC



180 amp welder
3 kW AC output
Honda engine/elect. start
GAW180HE



225 amp welder
6 kW AC output
Kubota diesel engine
SDW225SSA



300 amp welder
10.5 kW AC output
Kubota diesel engine
DLW300ESA



400 amp welder
14 kW AC output
Kubota diesel engine
DLW400ESA

500 amp welder
3 kW AC output
Kubota diesel engine
DAW500SA



*Some units shown on optional highway-ready trailers.
For more information, please see our full-line welder brochure.*

Portable Welder Specifications

MODEL	GAW135H	BDW180MC	GAW180HE	SDW225SSA	DLW300ESA	DLW400ESA	DAW500SA
WELDER FEATURES							
DC Voltage	25.2	26.8	26.8	15-28CV, 28CC	31CC	34, 2x27CC	16-40CV, 38CC
DC Current	135CC	170CC	180CC	225CC/CV	300CC/CV	400CC/CV 2x200CC/CV	500CC/CV
100% Duty Cycle @ 100%, amps	40% @ 135A	40% @ 120A	50% @ 180A	200	280	350/2x175	350
Current Range, amps	40-135	30-180	50-180	50-225	35-300	70-400, 2x35-200	40-500
DC Current — Constant Voltage	N/A	N/A	N/A	Standard	Standard	Standard	Standard
DC Current — Constant Current	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Welding Process — SMAW	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Welding Process — FCAW	Standard	N/A	Standard	Standard	Standard	Standard	Standard
Welding Process — GMAW	N/A	N/A	N/A	Standard	Standard	Standard	Standard
Welding Process — GTAW	N/A	Standard	Standard	Standard	Standard	Standard	Standard
Welding Process — ACAC	N/A	N/A	N/A	Standard	Standard	Standard	Standard
AC OUTPUT							
Maximum Output — AC kW Single Phase	1.5	N/A	3.0	6	10.5	14	3
Cycle	60	N/A	60	50/60	50/60	50/60	50/60
Voltage	120	N/A	120	120/240	120/240	120/240	120
Amperage	15	N/A	25	50/25	87/44	116/58	25
Voltage Regulation	3%	N/A	3%	2%	1.5%	1.5%	7%
Receptacles (see chart below)	A	N/A	A, C	A, C, F	E, C, H, A	A, C, E, H	A, C
ENGINE FEATURES							
Engine Model	Honda GX200	(5) 12V-12Ah Batteries	Honda GX340	Kubota Z482	Kubota D722	Kubota V1305	Kubota D1803
No. Cylinders; HP††; RPM	1; 6.5; 3600	N/A	1; 9.5; 3600	2; 12; 3600	3; 19; 3600	4; 31.5; 3600	3; 34.5; 2800
Fuel Type	Gasoline	N/A	Gasoline	Diesel	Diesel	Diesel	Diesel
Fuel Tank Capacity — gal.	1.6	N/A	3.7	6.6	9.5	11.1	12.0
Fuel Consumption at rated load — gph	0.46	N/A	0.93	0.6	1.1	1.5	1.3
Electric Start, Idle Switch	Recoil w/Idle	N/A	Standard	Standard	Standard	Standard	Standard
GENERAL FEATURES							
Simultaneous Use — AC/DC	No	N/A	Standard	Standard	Standard	Standard	Standard
Noise Level — dBA @ 23 feet	76	N/A	76	68.7	59	70	72
Lifting Bale	N/A	N/A	Standard	Standard	Standard	Standard	Standard
External Drains — Water	N/A	N/A	N/A	Standard	Standard	Standard	Standard
External Drains — Oil, Fuel	N/A	N/A	N/A	Standard	Standard	Standard	Standard
Automatic Safety Shutdown — Oil Pressure	Oil Level	N/A	Oil Level	Standard	Standard	Standard	Standard
Automatic Safety Shutdown — Water Temperature	N/A (Air Cooled)	N/A	N/A (Air Cooled)	Standard	Standard	Standard	Standard
Automatic Safety Shutdown — Thermal Switch DC	N/A	N/A	N/A	Standard	Standard	Standard	Standard
Automatic Safety Shutdown — Low Battery Charge	N/A	N/A	N/A	Standard	N/A	N/A	Standard
DIMENSIONS AND WEIGHT							
Dimensions — L x W x H in.	21.8 x 17.8 x 19	20.5 x 11.8 x 17.5	27.5 x 22 x 23.8	45 x 26 x 31	51 x 27 x 33	61 x 29 x 35	53 x 32 x 36
Dry Weight lbs.	114	129	239	671	849	1,090	1,069
OPTIONS							
Trailers	N/A	N/A	N/A	LTRL-10W*; TRLR-MPXF**	TRLR-10W; TRLR-MPXF**	TRLR-MP; TRLR- MPXF**	TRLR-MP; TRLR- MPXF**
Wheel Kit	UWK	Standard	UWK	WKT225A	N/A	N/A	N/A
Remote Control	N/A	N/A	N/A	Optional	Optional	Optional	Optional

*Requires adapter kit. ** TRLR-MPXF has built-in 28 gallon fuel cell

Welders Warranty: Models rated at 180 amps and below include a **two-year warranty** covering parts and labor. Models rated at 225 amps and above include a **three-year (or 3,000 hours) warranty** covering parts and labor. Contact Multiquip for complete warranty information.

RECEPTABLE IDENTIFICATION CHART

Match the letter codes in the specification table to the receptacles below.



A — NEMA 5-20R 125V duplex 20A w/GFCI



B — NEMA L5-20R 125V 20A twist lock

C — NEMA L5-30R 125V 30A twist lock



D — NEMA L6-20R 250V 20A twist lock

E — NEMA L6-30R 250V 30A twist lock



F — NEMA L14-30R 125/250V 30A twist lock



G — NEMA 7410 250V 20A twist lock



H — CS-6369 125/250VAC 50A twist lock

Portable Generator Specifications

MODEL	GA25H	GA29R	GA36HA	GA45RA	GA6HA	GA6HEA	GA6REA	GA97HE	DA7000SSA
Alternator Design	Brushless								
Maximum Watts	2,500	2,900	3,600	4,500	6,000	6,000	6,000	9,700	7,000
Continuous Watts	2,200	2,600	3,200	3,700	5,000	5,000	5,000	8,400	6,000
Voltage	120V			120/240V					
Max. Amp @ 120V	20.8	24.2	30	37.5	50	50	50	80.8	58.3
Cont. Amp @ 120V	18.3	21.7	26.6	30.8	41.6	41.6	41.6	70	50
Max. Amp @ 240V	N/A	N/A	15	18.75	25	25	25	40.4	29.2
Cont. Amp @ 240V	N/A	N/A	13.3	15.4	20.8	20.8	20.8	35	25
Frequency/Phase	60 Hz / Single phase								
Voltmeter	Standard								
Full Power Switch	N/A	Standard							
RECEPTACLES* AND CIRCUIT BREAKERS									
5-20R 125V GFCI 20A	✓	✓	✓ (2)	✓ (2)	✓ (2)	✓ (2)	✓ (2)	✓ (2)	✓
L5-20R 125V; T-Lock 20A	✓	✓	✓	✓	✓	✓	✓	✓	
L5-30R 125V; T-Lock 30A			✓	✓	✓	✓	✓	✓	✓
L6-20R 250V; T-Lock 20A									
L14-20R 125/250V; T-Lock 20A			✓	✓					
L14-30R 125/250V; T-Lock 30A					✓	✓	✓	✓	✓
CS-6369; 125/250VAC 50A									✓
Main Circuit Breaker	20A	22A	13.5A	15A	21A	21A	21A	35A	25A
Number of Poles	1			2					
ENGINE									
Engine Manufacturer	Honda	Robin	Honda	Robin	Honda	Honda	Robin	Honda	Kubota Diesel
Engine Model	GX-160	EX-17D	GX-240	EX-27D	GX-340	GX-340	EH-36	GX-610	Z482
Horsepower (KW) ‡‡	4.8 (4.1)	5.7 (4.2)	7.1 (5.3)	9.0 (6.7)	9.5 (7.1)	9.5 (7.1)	11.0 (8.25)	16.6 (12.4)	12.5 (9.3)
Rated Speed — RPM	3,600								
Low Oil Shutdown	Standard								
Starting Systems**	Recoil				Recoil/Elect.		Recoil/Elect.		Electric
Fuel Capacity — gal (ltr)	3.2 (12)	2.6 (10)	5.0 (19)	5.0 (19)	5.0 (19)	5.0 (19)	5.0 (19)	10.0 (37.8)	6.6 (25)
Running Time — hr./ tank***	6	5	5.5	5.5	5.5	5.5	5.5	6.75	10
Fuel Gauge	Standard								
Automatic Idle Control	N/A		Standard						
Sound Level dB @ 23 ft.	70	71	73	75	76	76	81	78	65.7
DIMENSIONS AND WEIGHT									
Length — in. (cm)	20 (51)	20 (51)	24½ (62)	24½ (62)	25½ (65)	26½ (67)	26½ (67)	31¼ (79)	46 (117)
Width — in. (cm)	16 (41)	16 (41)	22¼ (57)	22¼ (57)	22½ (57)	22¼ (56)	22¼ (56)	21¼ (54)	26 (66)
Height — in. (cm)	18¾ (48)	18 (46)	21½ (55)	21½ (55)	21½ (55)	22½ (57)	22½ (57)	27½ (70)	31½ (80)
Dry Weight — lbs. (kg)	107 (49)	108 (49)	171 (78)	159 (72)	194 (88)	203 (92)	204 (93)	327 (148)	571 (259)
OPTIONS									
Wheel Kit	UWK						WKT-97		WKT225A
Trailer	N/A								TRLR10W‡

© COPYRIGHT 2009, MULTIQUP INC.

‡‡ Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. Multiquip Inc. and its subsidiary companies makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy of the engine power rating. Users are advised to consult the engine manufacturer's owners manual and its website for specific information regarding the engine power rating.

* See receptacle chart on Page 7.

** Electric start models are shipped less battery.

*** All running times computed at full load using fuel consumption rates supplied by engine manufacturer.

‡ Requires adapter kit.

Note: Some units may be shown with optional equipment.



MULTIQUP INC.
 POST OFFICE BOX 6254
 CARSON, CA 90749
 310-537-3700 • 800-421-1244
 FAX: 310-537-3927
 E-MAIL: mq@multiquip.com
 www.multiquip.com